



DG4V-5-6CJ-M-U-H7-22, DG4V56CJMUH722

829AN00100A [↗](#)**Where to buy** [↗](#)

Product specifications

Characteristic	Value
Actuation type	Solenoid operated
Brand	Vickers by Danfoss
Coil Rating	24 VDC
Design series	22 Series
Electrical connection	ISO 4400 (Din 43650) connector
Energy Time	120-45 ms
Flow rate upto GPM	32.0
Flow rate upto LPM	120.0
Fluid cleanliness	19/17/14 micron
Fluid compatibility	Petroleum oils
Indicator Light	No
Interface	ISO4401-05
Manual override	Plain
Model Code	DG4V56CJMUH722
Performance	High performance
Power Consumption	38 watt
Pressure rating PSI	4500
Pressure rating BAR	315
Seal type	Viton
Solenoid Energising ID	Standard as per ANSI B93 9
Special features	None



Characteristic	Value
Spool Position Monitor	No
Spool type	Spool 6
Spring Arrangement	Spring centred
Stage	Single stage
Surge Suppr Damper	No
Tank port rating BAR	210.0
Tank port rating PSI	3000
Valve mount type	Subplate/manifold mounted
Valve type	Directional control valve
Working temp max C	70
Working temp max F	158
Working temp min C	-20
Working temp min F	-4

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)